

Principal Dimension

External Dimension		Internal Dimension	
Length	12,192 mm	Length between end panels	12,172 mm
		Length between corner posts	11,615 mm
Width	2,438 mm	Platform width	2,374 mm
Height (without extension)	2,591 mm	Height (without extension)	1,956 mm
Height (max extension)	4,115 mm	Height (max extension)	3,483 mm

Height extension table				
Steps	External Dimension		Internal Dimension	
Without Extension	8' 6"	(2,591 mm)	6' 5"	(1,959 mm)
1st Step	9' 6"	(2,896 mm)	7' 5"	(2,264 mm)
2nd Step	10' 6"	(3,200 mm)	8' 5"	(2,568 mm)
3rd Step	11' 6"	(3,505 mm)	9' 5"	(2,873 mm)
4th Step	12' 6"	(3,810 mm)	10' 5"	(3,178 mm)
5th Step	13' 6"	(4,115 mm)	11' 5"	(3,483 mm)

Weight and Others	
Tare Weight	5,600 kg
Payload	39,400 kg
Gross Weight	45,000 kg
Stack Weight (8'6" ~ 13'6")	192,000 kg
Folded Height	648 mm (to fold 4 units into 2,591 mm)
Certification	CSC, TCT
Classification	BV, GL, ABS and KR
Counterbalance Device	Hydraulic Cushioning Cylinder and Coil Spring